# Instability of sliding viscoplastic films

## Thomasina V. Ball<sup>1</sup> & Neil J. Balmforth<sup>1</sup>

<sup>1</sup>Department of Mathematics, University of British Columbia, Vancouver, BC, V6T 1Z2, Canada

(Received xx; revised xx; accepted xx)

The stability of sliding spreading films of Herschel-Bulkley fluid is investigated theoretically, motivated by a dramatic fingering pattern observed experimentally and proposed theoretically to originate from an extensional flow instability of shear-thinning fluids. Considering the thin-film limit, we construct axisymmetrical base states and then test their stability towards non-axisymmetrical perturbations by numerically solving the initial-value problem. We complement the numerics with analytical solutions for early and late times. The stability analysis demonstrates that spreading thinning films are unstable. At late times, where the spreading of the base state becomes self-similar, nonaxisymmetrical patterns can develop strongly if the fluid has a yield stress or is sufficiently shear thinning.

## 1. Introduction

Shallow films of spreading fluid feature in a wide variety of problems in the geosciences and engineering. In a number of settings, the film spreads with little traction over a surface, and the main resistance to flow then stems from the extensional stresses of the material, rather than the vertical shear stresses (which control shallow flow over a sticky substrate). For thin viscous flow, a common approach is then to exploit the low aspect ratio of the film to develop a free-film model to compactly capture the spreading dynamics (Oron et al. 1997; Craster & Matar 2009). This type of approach has been exploited to explore, for example, the spreading of oil over a fluid surface (di Pietro & Cox 1979; Koch & Koch 1995), and generalized to power-law fluids to describe the motion of ice streams and shelves (MacAyeal & Barcilon 1988; MacAyeal 1989; Schoof & Hewitt 2013; Pegler et al. 2012) or the deformation of the Earth's crust (England & McKenzie 1982, 1983). Even when the surface over which the fluid flows would normally satisfy a no-slip condition, the phenomenon of effective slip (Barnes 1995) may lubricate a polymeric fluid to the degree that the spreading dynamics becomes more comparable to a free film (Liu et al. 2018). Alternatively, the surface can be treated to promote significant sliding of such fluids (Luu & Forterre 2009, 2013).

Although experiments with radially spreading free viscous films have suggested that the flow is stable towards non-axisymmetrical disturbances (Pegler & Worster 2012; Sayag & Worster 2019*a*), shear-thinning suspensions suffer a dramatic instability (Sayag *et al.* 2012; Sayag & Worster 2019*a*). An illustration of this type of instability is displayed in figure 1, which shows an experiment in which an aqueous suspension of Carbopol is extruded from a vent onto a shallow bath of water. Such suspensions are viscoplastic fluids, possessing both a yield stress and shear-thinning plastic viscosity (Balmforth *et al.* 2014). The Xanthan gum solutions used by Sayag *et al.* are more commonly modelled without a yield stress (athough one can be measureable at sufficiently high concentration). Despite this, and the much deeper baths over which they floated the Xanthan gum, the fingers seen in figure 1 are striking similar to those reported by Sayag *et al.* and also



FIGURE 1. An experiment in which an aqueous suspension of Carbopol (with a density that is almost matched with water) is extruded from a vent onto a launch stage and then onto a shallow bath of dyed water, as sketched in (a). The pump rate is  $Q \simeq 5$ ml/min, the launch stage has diameter 5cm and the water depth is about 3mm; a Herschel-Bulkley fit to the Carbopol rheology provided by a rheometer is  $(n, \tau_Y, K) = (0.41, 8.0 \text{Pa}, 5.9 \text{Pa} \text{s}^n)$ . Panels (b)–(e) show photographs (from above) at the times indicated (the spatial scale is indicated by the diameter of the launch stage). In (f) we show snapshots of the outline of the Carbopol, equally spaced and coloured by time; the dashed circle identifies the launch stage and the inset shows the initial condition from which pumping commenced. In (g) we plot the light intensity transmitted through the dyed water along the cross-sections through each of the six fingers shown in (e). The light intensity corresponding to the water bath is shown by the grey bar. The variation of this intensity along the finger indicates the local depth of water below the finger, with a measurement close to 0.5 suggesting very little water underneath the central parts of the fingers, and the lower values near the stage and flow front implying deeper underlying water.

reported anecdotally in the squeeze flow of pastes and cement (Roussel *et al.* 2006; Mascia *et al.* 2006).

To rationalize their observations, Sayag & Worster (2019b) analyzed the stability of radial extensional flow of a power-law fluid in two dimensions in the inertialess limit (*cf.* Sayag (2019) for the stability of extensional flow of a power-law fluid on a sphere). They observed that non-axisymmetrical perturbations could grow exponentially for limited durations of time, provided the fluid was shear thinning. Nevertheless, the experiments feature expanding fluid films that thin as they flow radially and possess a three-dimensional stress state, both of which may affect the linear stability. Moreover, although the degree of instabilility becomes pronounced as the fluid is made more shear thinning, the finite duration over which linear modes are unstable, and the potentially stronger damping incurred at earlier and later times, may lessen the impact for typical laboratory experiments. In particular, focussing purely on the intervals over which angular modes have a positive instantaneous growth rate can be misleading in comparison to their net amplification (Ball *et al.* 2020*a*). The fingering patterns in radial extensional flows in both Hele-Shaw cells and like that shown in figure 1 may, in fact, have an entirely different explanation in terms of the fracture under tension of the material, facilitated by the presence of water (Ball *et al.* 2020*a*,*b*).

In view of these concerns, we therefore revisit Sayag & Worster's stability analysis but in the context of three-dimensional, thinning films. Moreover, to generalize the theory to apply to viscoplastic films such as the Carbopol experiments shown in figure 1, we consider a more general constitutive law. In particular we study shallow, spreading films of Herschel-Bulkley fluid. We thereby assess the impact of both the structure of the extensional flow and a yield stress on Sayag & Worster's instability.

In section 2, we formulate the theoretical problem and provide some details of the viscoplastic version of the asymptotic reduction that furnishes a free-film-type model. In section 3, we consider axisymmetrical spreading, constructing the base state for the stability analysis conducted in section 4. The base state corresponds to the viscoplastic generalization of the solutions provided by Pegler & Worster (2012) for spreading viscous films. Additional details of the analysis of some asymptotic limits are provided in the Appendices.

## 2. Formulation

Consider the spreading of a viscoplastic film that slides without friction over a horizontal surface. The flow is fed by a source located at an inner radius  $r_v$  that delivers a constant flux Q with a prescribed depth. A key feature of the flow is that it is shallow, with a typical vertical lengthscale  $\mathcal{H}$  that is much smaller than a characteristic horizontal (radial) scale  $\mathcal{L}$ . We set  $\epsilon = \mathcal{H}/\mathcal{L} \ll 1$  for the typical aspect ratio, and define a characteristic horizontal flow speed,  $\mathcal{V} = Q/(\mathcal{HL})$ . We choose  $\mathcal{L} \equiv r_v$ , but leave the vertical lengthscale  $\mathcal{H}$  free for the moment, demanding only that the incoming flow depth at the vent is of order  $\mathcal{H}$ .

In cylindrical polar coordinates,  $(r, \vartheta, z)$ , the governing equations for an incompressible fluid with negligible inertia and velocity field  $\boldsymbol{u} = (u, v, w)$  are

$$\boldsymbol{\nabla} \cdot \boldsymbol{u} = \boldsymbol{0}, \tag{2.1}$$

$$0 = -\nabla p + \nabla \cdot \tau + \rho \mathbf{g}, \qquad (2.2)$$

where  $\rho$  and  $\mathbf{g} = (0, 0, -g)$  are density and gravity, and the deviatoric stress tensor and pressure are  $\tau$  and p. The Herschel-Bulkley constitutive law is

$$\dot{\boldsymbol{\gamma}} = \boldsymbol{0}, \qquad \tau < \tau_{\mathrm{Y}}, \\ \boldsymbol{\tau} = \left( K \dot{\boldsymbol{\gamma}}^{n-1} + \frac{\tau_{\mathrm{Y}}}{\dot{\boldsymbol{\gamma}}} \right) \dot{\boldsymbol{\gamma}}, \quad \tau \ge \tau_{\mathrm{Y}},$$
(2.3)

where  $\tau_{\rm Y}$ , K and n represent the yield stress, consistency and power-law index, and the deformation rates are given by

$$\dot{\boldsymbol{\gamma}} = \begin{pmatrix} 2u_r & r^{-1}(u_{\vartheta} - v) + v_r & u_z + w_r \\ r^{-1}(u_{\vartheta} - v) + v_r & 2(u + v_{\vartheta})/r & v_z + r^{-1}w_{\vartheta} \\ u_z + w_r & v_z + r^{-1}w_{\vartheta} & 2w_z \end{pmatrix},$$
(2.4)

and the scalars,  $\dot{\gamma} = \sqrt{\frac{1}{2}\sum_{j,k}\dot{\gamma}_{jk}^2}$  and  $\tau = \sqrt{\frac{1}{2}\sum_{j,k}\tau_{jk}^2}$ , denote tensorial invariants.

Above, and hereon, we use subscript to represent partial derivatives, except when referring to tensor components or the yield stress (which are further distinguished by a different font style).

At the top surface of the fluid, located by  $z = h(r, \vartheta, t)$ , we have the kinematic and stress conditions,

$$h_t + uh_r + r^{-1}h_\vartheta = w, (2.5)$$

$$(\boldsymbol{\tau} - p\boldsymbol{I}) \cdot \hat{\boldsymbol{n}} = \boldsymbol{0}, \qquad (2.6)$$

(ignoring surface tension), where  $\hat{\boldsymbol{n}}$  is the unit normal vector and  $\boldsymbol{I}$  is the identity. On the underlying surface z = 0, free sliding without penetration demands  $\tau_{\rm rz} = \tau_{z\theta} = w = 0$ .

#### 2.1. Reduced model

We remove dimensions from the equations by scaling vertical and radial distances by  $\mathcal{H}$ and  $\mathcal{L}$ , the horizontal velocity components u and v by  $\mathcal{V} = Q/(\mathcal{HL})$ , the vertical velocity w by  $\epsilon \mathcal{V}$ , and time by  $\mathcal{L}/\mathcal{V}$ . The stresses and pressure can then be scaled by the hydrostatic measure  $\rho g \mathcal{H}$ . The net effect of these scalings is to replace the gravity term in (2.2) by the unit vertical vector, and make the replacement  $K\dot{\gamma}^{n-1} + \tau_{\rm Y}\dot{\gamma}^{-1} \rightarrow \dot{\gamma}^{n-1} + \mathrm{Bi}\dot{\gamma}^{-1}$  in the constitutive law (2.3), where the dimensionless yield stress, or Bingham number, is

$$\mathrm{Bi} = \frac{\tau_{\mathrm{Y}} \mathcal{H}^n \mathcal{L}^{2n}}{KQ^n},\tag{2.7}$$

once we make the convenient choice for the vertical lengthscale,

$$\mathcal{H}^{1+n} = \frac{KQ^n}{\rho g \mathcal{L}^{2n}}.$$
(2.8)

When the dome is able to slide freely, the extensional and horizontal shear stresses control the spreading of a shallow fluid layer and vertical shear stresses remain weak (Liu *et al.* 2018; Balmforth 2018). The flow becomes plug-like throughout its depth, with horizontal velocity components,  $u \sim u(r, \vartheta, t) + O(\epsilon^2)$  and  $v \sim v(r, \vartheta, t) + O(\epsilon^2)$ . The preceding scalings then ensure that the extensional and horizontal shear stresses counter the pressure gradients in the force balance equations. Also, in view of (2.4), the vertical shear rates  $\dot{\gamma}_{rz}$  and  $\dot{\gamma}_{\theta z}$  are  $O(\epsilon)$  in comparison to the other components of the deformation rate tensor, a discrepancy that carries over to the stress components in view of the constitutive law. We therefore set  $(\tau_{rz}, \tau_{z\theta}) = \epsilon(\tilde{\tau}_{rz}, \tilde{\tau}_{z\theta})$ , reducing the force balance equations to

$$\frac{\partial p}{\partial r} = \frac{1}{r} \frac{\partial}{\partial r} (r\tau_{\rm rr}) + \frac{1}{r} \frac{\partial \tau_{\rm r\theta}}{\partial \vartheta} - \frac{\tau_{\theta\theta}}{r} + \frac{\partial \tilde{\tau}_{\rm rz}}{\partial z}, \qquad \frac{1}{r} \frac{\partial p}{\partial \vartheta} = \frac{1}{r^2} \frac{\partial}{\partial r} (r^2 \tau_{\rm r\theta}) + \frac{1}{r} \frac{\partial \tau_{\theta\theta}}{\partial \vartheta} + \frac{\partial \tilde{\tau}_{z\theta}}{\partial z}, \quad (2.9)$$

$$\frac{\partial p}{\partial z} + 1 - \frac{\partial \tau_{zz}}{\partial z} = O(\epsilon^2), \qquad (2.10)$$

along with the surface stress conditions,

$$\tilde{\tau}_{\rm rz} + h_r (p - \tau_{\rm rr}) - r^{-1} h_\vartheta \tau_{\rm r\theta} = 0, \qquad (2.11)$$

$$\tilde{\tau}_{z\theta} - h_r \tau_{r\theta} + r^{-1} h_{\vartheta} (p - \tau_{\theta\theta}) = 0, \qquad (2.12)$$

$$p - \tau_{\rm zz} = O(\epsilon^2), \tag{2.13}$$

at  $z = h(r, \vartheta, t)$ . Thus,  $p = \tau_{zz} + h - z$ .

Introducing this pressure solution into (2.9), then integrating these relations and the continuity equation (2.1) over the fluid depth (bearing in mind the plug-like form of the

horizontal velocity components, the stress boundary conditions and the surface kinematic condition (2.5)) gives

$$hh_r - [h(2\tau_{\rm rr} + \tau_{\theta\theta})]_r - \frac{1}{r} (h\tau_{\rm r\theta})_{\vartheta} + \frac{h}{r} (\tau_{\theta\theta} - \tau_{\rm rr}) = 0, \qquad (2.14)$$

$$\frac{hh_{\vartheta}}{r} - \frac{1}{r} \left[ h(2\tau_{\theta\theta} + \tau_{\rm rr}) \right]_{\vartheta} - \left( h\tau_{\rm r\theta} \right)_r - \frac{2}{r} h\tau_{\rm r\theta} = 0, \qquad (2.15)$$

$$h_t + \frac{1}{r}(rhu)_r + \frac{1}{r}(vh)_{\vartheta} = 0,$$
 (2.16)

where, on dropping the vertical shear rates, the leading-order constitutive law implies

$$\left[\tau_{\rm rr}, \tau_{\theta\theta}, \tau_{\rm r\theta}\right] = \left(\frac{{\rm Bi}}{\dot{\gamma}} + \dot{\gamma}^{n-1}\right) \left[2u_r, \frac{2}{r}(u+v_\vartheta), \frac{1}{r}(u_\vartheta - v) + v_r\right],\tag{2.17}$$

with  $\dot{\gamma} = \sqrt{\dot{\gamma}_{\rm rr}^2 + \dot{\gamma}_{\rm r\theta}^2 + \dot{\gamma}_{\theta\theta}^2 + \dot{\gamma}_{\rm rr} \dot{\gamma}_{\theta\theta}}$ .

Finally, we state the radial boundary conditions, which follow conveniently for the reduced model by imposing net force balance at the outer edge and flux balance at the inner edge or vent. The outer edge of the dome is defined as  $r = R(\vartheta, t)$ . Here, the kinematic and stress conditions demand

$$R_t + \frac{v}{R}R_\vartheta = u, \qquad (2.18)$$

$$\frac{1}{2}h^2 - h\left[\tau_{\rm rr} + \tau_{\theta\theta} + \frac{R}{\sqrt{R^2 + R_{\vartheta}^2}}\left(\tau_{\rm rr} - 2\frac{R_{\vartheta}}{R}\tau_{\rm r\theta} + \frac{R_{\vartheta}^2}{R^2}\tau_{\theta\theta}\right)\right] = 0, \qquad (2.19)$$

$$\tau_{\mathrm{r}\theta} - \frac{R_{\vartheta}}{R} (\tau_{\theta\theta} - \tau_{\mathrm{rr}}) - \frac{R_{\vartheta}^2}{R^2} \tau_{\mathrm{r}\theta} = 0.$$
(2.20)

At the inner vent r = 1, we impose the incoming flux and depth:

$$2\pi H_0 u(1,\vartheta,t) = 1, \quad h(1,\vartheta,t) = H_0, \quad v(1,\vartheta,t) = 0.$$
(2.21)

The model in (2.14)-(2.16) amounts to the viscoplastic generalization of models of free (inertialess) viscous films (Oron *et al.* 1997; Craster & Matar 2009). With  $Bi \rightarrow 0$ , we recover the power-law fluid model popular for ice shelves (ignoring any buoyancy due to flotation over an underlying ocean) and streams (MacAyeal & Barcilon 1988; MacAyeal 1989; Schoof & Hewitt 2013; Pegler *et al.* 2012), and similar to that proposed for crustal deformation (England & McKenzie 1982, 1983). The viscoplastic model in (2.16)-(2.15) has been considered previously in exploring the collapse by sliding of axisymmetric or planar reservoirs (Liu *et al.* 2018; Balmforth 2018).

## 3. Axisymmetrical spreading

Axisymmetrical spreading states with

$$h = H(r,t), \ u = U(r,t), \ v = 0, \ R = \overline{R}(t), \ [\tau_{\mathrm{rr}}, \tau_{\mathrm{r}\theta}, \tau_{\theta\theta}] = [T_{\mathrm{rr}}(r,t), T_{\mathrm{r}\theta}(r,t), T_{\theta\theta}(r,t)]$$

satisfy the equations

$$HH_{r} - [H(2T_{rr} + T_{\theta\theta})]_{r} + \frac{H}{r}(T_{\theta\theta} - T_{rr}) = 0, \qquad (3.1)$$

$$H_t + \frac{1}{r}(rHU)_r = 0, (3.2)$$

T. V. Ball & N. J. Balmforth

$$[T_{\rm rr}, T_{\theta\theta}] = \left(\frac{\rm Bi}{\dot{\Gamma}} + \dot{\Gamma}^{n-1}\right) \left[2U_r, \frac{2U}{r}\right], \qquad \dot{\Gamma} = 2\sqrt{U_r^2 + \frac{1}{r}UU_r + \frac{1}{r^2}U^2}, \qquad (3.3)$$
with the boundary conditions

along with the boundary conditions,

$$\overline{R}_{t} = U(\overline{R}, t), \quad \left[\frac{1}{2}h^{2} - h(2T_{rr} + T_{\theta\theta})\right]_{r=\overline{R}} = 0, \quad 2\pi H_{0}U(1, t) = 1, \quad H(1, t) = H_{0}.$$
(3.4)

For the initial conditions, we use  $\overline{R}(0) = 1 + 10^{-4}$  and  $H(r,0) = H_0$ , which ease the computation of numerical solutions by commencing with a finite domain.

#### 3.1. Generalized Newtonian limit

As shown by Pegler & Worster (2012) and illustrated in figure 2, a freely sliding, Newtonian current converges to steady profile as it expands away from the vent, with the outer edge approaching a constant speed. The steady profile corresponds to a constantflux, time-independent solution to (3.1)-(3.4) with a fixed outer edge (also displayed in the figure). The profile is characterized by an adjustment near the vent over which the depth adjusts from the value set at the vent to that for the  $H_0$ -independent solution,

$$H \sim r^{-1} \sqrt{3/\pi}, \quad U \sim (2\pi)^{-1} \sqrt{\pi/3},$$
 (3.5)

which satisfies (3.1)-(3.4) but for the stress condition at the outer edge. In the solutions of the initial-value problem, the stress condition forces a departure from (3.5) over a region near the outer edge, where the solution remains time-dependent and given by a local similarity solution of the form  $U = \mathcal{U}(\zeta)$ ,  $H = t^{-1}F(\zeta)$  and  $\zeta \propto r/t$  (cf. Pegler & Worster (2012); Appendix A.1). The outer edge is

$$\overline{R} \sim 1 + \Lambda t, \quad \Lambda \approx 0.173,$$
(3.6)

which is compared with the numerical solutions of the initial-value problem in figure 2.

This Newtonian behaviour generalizes to the case of a power-law fluid ( $n \neq 1$  and Bi = 0): as illustrated in figure 3, the sliding current again converges to a steady profile except near the outer edge. The steady,  $H_0$ -independent, constant flux solution generalizing (3.5) is

$$H \sim \tilde{H}_0 r^{-2n/(n+1)}, \quad U \sim (2\pi \tilde{H}_0)^{-1} r^{-(1-n)/(n+1)},$$
(3.7)

with

$$\tilde{H}_0 = \left[\frac{(3n^2+1)^{\frac{1}{2}(n-1)}(6n^2-n+1)}{n(n+1)^n\pi^n}\right]^{\frac{1}{n+1}}.$$
(3.8)

The time-dependent region bordering the outer edge now has the self-similar form,  $H = t^{-n}F(\zeta)$   $U = t^{-\frac{1}{2}(1-n)}\mathcal{U}(\zeta)$  and  $\zeta \propto rt^{-\frac{1}{2}(1+n)}$ , which is explored in more detail in Appendix A.1. The self-similar form indicates that the fluid depth at the outer edge is  $H(R,t) \propto t^{-n}$ , as seen in figure 2(d) (for the Newtonian case, Pegler & Worster established  $H(R,t) \sim 4t^{-1}$ ). The radial expansion of the outer edge is given by

$$\overline{R} \sim 1 + \Lambda t^{\frac{1}{2}(1+n)},\tag{3.9}$$

where  $\Lambda$  depends on n; for n = 0.4,  $\Lambda = 0.328$  which is again compared with the numerical solutions in figure 3. A more detailed illustration of the approach of the solutions to the self-similar form with n = 1 and n = 0.4 is shown in figure 4.

The convergence of the steady states to (3.5) or (3.7) therefore guarantees that the initial depth  $H_0$  has little impact on the evolution, and the self-similar structure at the edge permits the current to become steady behind the flow front. At late times, the



FIGURE 2. Sample Newtonian solutions (n = 1, Bi = 0), showing snapshots (with colour representing time) of (a) H(r,t) and (b) U(r,t), and time series of (c)  $\overline{R}(t)$  and (d)  $H_{min}(t) = H(\overline{R},t)$  for  $H_0 = 0.5$ , 1 and 2. The times of the snapshots are indicated in (c) and (d). The insets in (a) and (b) show the corresponding, true, steady solutions with a fixed outer radius given by that of the final solutions to the initial-value problem. Also included in (c) and (d) are the results for the solutions for power-law fluid shown in figure 3. The dots in (c) show the predictions in (3.6) and (3.9); in (d), the dots show  $4t^{-1}$  and  $0.8t^{-0.4}$ .

self-similar structure occupies the bulk of the current. By contrast, as we see below, because the rates of extension decay with radius, the effect of the yield stress gradually amplifies towards the outer edge when  $Bi \neq 0$ . This prevents any approach to such a steady profile, qualitatively changing the spreading dynamics and introducing a different self-similar late-time structure.



FIGURE 3. Solutions for power-law fluid (n = 0.4, Bi = 0), showing snapshots (colour representing time) of (a) H(r, t) and (b) U(r, t), for  $H_0 = 1$ , 1.5 and 2. The time series of  $\overline{R}(t)$  for these solutions is included in figure 2(c), as well as the times of the snapshots. The insets show the corresponding, true, steady solutions with a fixed outer radius given by that of the final solutions to the initial-value problem. The dots show (3.7) and (3.9).

#### 3.2. Sample numerical solutions

Figure 5 displays a numerical solution to (3.1)-(3.4) for n = 0.4 and  $\text{Bi} = H_0 = 1$ . For this viscoplastic material, the fluid initially expands outwards at constant speed, but the advance then slows, damming up the flow and causing the dome to deepen near the vent. The dynamics is therefore different to that for a Newtonian or power-law fluid (Bi = 0). In particular, the expansion of the viscoplastic dome slows towards the weaker advance  $R \propto t^{1/2}$  over long times, and the dome continues to thicken at the vent and thin at the outer edge.

As shown in figure 6, varying the depth at the vent,  $H_0$ , alters the solution at earlier times, delaying the build up of material nearby. However, the solutions with different  $H_0$ subsequently converge to similar forms over longer times and larger radii. Thus, aside from a thin region near the vent, the solutions again become insensitive to  $H_0$ .

The viscoplastic evolution over even longer times is illustrated in figure 7 (for n = Bi = 1). This example shows more clearly the convergence of the outer radius to  $\overline{R} \sim \Lambda \sqrt{t/\text{Bi}}$ , for a constant  $\Lambda \approx \frac{1}{2}$  and dependence on Bi that is rationalized below. We further plot snapshots of the solution against the scaled radial coordinate  $\zeta = r/\overline{R}(t)$  and scale the horizontal flow speed U(r,t) by  $\Lambda \sqrt{t\text{Bi}}$ . The rescalings emphasize how the solution converges to a self-similar form in which  $H \sim \text{Bi}F(\zeta)$  and  $U \sim \Lambda \mathcal{U}(\zeta)/\sqrt{t\text{Bi}}$ , with



FIGURE 4. A comparison of numerical solutions of the initial-value problem (solid lines) with self-similar solutions (dots) for (a) Newtonian (n = 1, Bi = 0) and (b) power-law fluid (n = 0.4, Bi = 0). Plotted are the scaled variables  $t^{\frac{1}{2}(1-n)}(r/\overline{R})^{-(1-n)/(n+1)}U \equiv \zeta^{-(1-n)/(n+1)}U(\zeta)$  and  $t^n(r/\overline{R})^{2n/(n+1)}H \equiv \zeta^{2n/(n+1)}F(\zeta)$  against  $\zeta \equiv r/\overline{R}(t)$  every 100 time units. The two panels present the initial-value problem solutions shown in figures 2 and 3, with colour again representing time (from red to blue, as indicated by the arrows), and omitting the earliest snapshot in each computation.

 $\zeta = r\sqrt{\text{Bi}/t}/\Lambda$ . Such self-similar solutions arise because the decline of the strain rates over long times paves the way to a plastic limit of the problem in (2.14)-(2.21). This limit is analyzed in more detail in §3.4, which provides a direct construction of the self-similar states. That corresponding to the long-time limit of the solution of the initial-value problem in figure 7 is also included there for comparison.

## 3.3. Early time solution, $t \ll 1$

For small times, we set  $r = 1 + \delta x$  and  $t = \delta \hat{t}$ , where  $\delta \ll 1$  and x and  $\hat{t}$  are O(1). In this limit, the variables remain close to their values at vent and so

 $H = H_0 + \delta H_1(x, \hat{t}), \qquad U = (2\pi H_0)^{-1} + \delta U_1(x, \hat{t}), \qquad \overline{R} = 1 + \delta \overline{R}_1(\hat{t}).$ 

At leading order, (3.1) and (3.3) become

$$\frac{\partial}{\partial x} \left[ \frac{1}{2} H_0^2 - H_0 (2T_{\rm rr} + T_{\theta\theta}) \right] = 0, \qquad (3.10)$$

$$(T_{\rm rr}, T_{\theta\theta}) = \left(\frac{\rm Bi}{\dot{\Gamma}} + \dot{\Gamma}^{n-1}\right) \left(2U_{1x}, \frac{1}{\pi H_0}\right), \qquad \dot{\Gamma} = \sqrt{\left(2U_{1x} + \frac{1}{2\pi H_0}\right)^2 + \frac{3}{4\pi^2 H_0^2}}.$$
(3.11)

T. V. Ball & N. J. Balmforth



FIGURE 5. Sample solution for n = 0.4 and Bi  $= H_0 = 1$ , showing snapshots of (a) H(r, t) and (b) U(r, t), and time series of (c)  $\overline{R}(t) - 1$  and (d)  $H_{max}(t)$  (solid) and  $H_{min}(t)$  (dashed). The stars in (c) and (d) indicates the times of the snapshots in (a) and (b). Slopes of unity and  $\frac{1}{2}$  are indicated in (c).



FIGURE 6. Sample snapshots of H(r, t) for n = 0.4 and Bi = 1 for varying  $H_0$ . The inset shows time series of  $\overline{R}(t)$ .

In view of the stress conditions at the edge, we therefore have

$$\frac{1}{4}H_0\dot{\Gamma} = (\mathrm{Bi} + \dot{\Gamma}^n)\sqrt{\dot{\Gamma}^2 - \frac{3}{4\pi^2 H_0^2}}, \qquad U_{1x} = \frac{1}{2}\sqrt{\dot{\Gamma}^2 - \frac{3}{4\pi^2 H_0^2}} - \frac{1}{4\pi H_0}.$$
 (3.12)

That is,  $U_{1x}$  is constant, and so  $U = (2\pi H_0)^{-1} + U_{1x}(r-1)$  in terms of the original variables. For Bi  $\gg 1$ , we arrive at the limit,

$$\dot{\Gamma} \to \frac{\sqrt{3}}{2\pi H_0}, \qquad U_{1x} \to -\frac{1}{4\pi H_0},$$
(3.13)



FIGURE 7. Numerical solution for  $n = \text{Bi} = H_0 = 1$ , showing snapshots of (a) H(r,t)/Bi and (b)  $U(r,t)\sqrt{t\text{Bi}}/\Lambda$  every 100 time units, plotted against  $r/\overline{R}(t)$ , with  $\Lambda \approx \frac{1}{2}$ . The dots and darker (blue) line show the self-similar solution of §3.4 with  $\varepsilon \ll 1$ . In (c) and (d), we plot times series of  $\overline{R}(t)$ ,  $H_{max}(t)$  (solid) and  $H_{min}(t)$  (dashed). The dashed line in (c) shows  $\overline{R} = \Lambda\sqrt{t/\text{Bi}}$ , and the initial linear scaling is indicated. In (e) and (f), solutions with  $H_0 = 1, 2, 4, 6, 8$  and 12 are plotted at the times indicated and again compared with the similarity solution; time series of the edge  $\overline{R}(t)$  for the solutions with  $H_0 > 1$  are included in (c) as the lighter grey lines, and (d) includes  $H_{max}(t)$  and  $H_{min}(t)$  for  $H_0 = 2$  and 4.

whereas for a Newtonian fluid,

$$\dot{\Gamma} \to \frac{1}{4\pi H_0} \sqrt{12 + \pi^2 H_0^4}, \qquad U_{1x} \to \frac{\pi H_0^2 - 2}{8\pi H_0}.$$
 (3.14)

Hence, U always decreases away from the vent in the plastic limit, but more generally it may increase for a sufficiently deep inflow.

Continuing on, the mass conservation and kinematic conditions become

$$H_{1\hat{t}} + H_0 U_{1x} + \frac{H_{1x}}{2\pi H_0} + \frac{1}{2\pi} = 0 \qquad \& \qquad \overline{R}_{1\hat{t}} = (2\pi H_0)^{-1}.$$
(3.15)

The first can be solved using the method of characteristics, noting that  $H_1 = 0$  for x = 0. In terms of the original variables, we find

$$H = H_0 - H_0 (1 + 2\pi H_0 U_{1x})(r - 1) \qquad \& \qquad \overline{R} = 1 + (2\pi H_0)^{-1} t.$$
(3.16)

## 3.4. Plastic similarity solution in the long-time limit

In the plastic limit,  $\dot{\Gamma} \rightarrow 0,$  the system (2.14)-(2.21) admits a similarity solution described by

$$\zeta \equiv \frac{\mathrm{Bi}^{1/2}r}{\Lambda t^{1/2}}, \quad F(\zeta) \equiv \frac{H}{\mathrm{Bi}}, \quad \mathcal{U}(\zeta) \equiv \Lambda^{-1}(t\mathrm{Bi})^{1/2}U, \quad [\mathcal{T}_{\mathrm{rr}}(\zeta), \mathcal{T}_{\theta\theta}(\zeta)] \equiv \mathrm{Bi}^{-1}[T_{\mathrm{rr}}, T_{\theta\theta}],$$
(3.17)

and satisfying

$$0 = FF_{\eta} - \left[F(2\mathcal{T}_{\mathrm{rr}} + \mathcal{T}_{\theta\theta})\right]_{\zeta} + \left(\mathcal{T}_{\theta\theta} - \mathcal{T}_{\mathrm{rr}}\right)\frac{F}{\zeta},\tag{3.18}$$

$$\left(\mathcal{T}_{\mathrm{rr}}, \mathcal{T}_{\theta\theta}\right) = \left(\mathcal{U}_{\zeta}^{2} + \frac{1}{\zeta}\mathcal{U}\mathcal{U}_{\zeta} + \frac{1}{\zeta^{2}}\mathcal{U}^{2}\right)^{-\frac{1}{2}} \left(\mathcal{U}_{\zeta}, \frac{\mathcal{U}}{\zeta}\right), \qquad (3.19)$$

$$\frac{1}{2}\zeta^2 F_{\zeta} = \left(\zeta \mathcal{U}F\right)_{\zeta},\tag{3.20}$$

subject to

$$\mathcal{U}(1) = \frac{1}{2} \quad \text{and} \quad \left[\frac{1}{2}F^2 - F\left(2\mathcal{T}_{\mathrm{rr}} + \mathcal{T}_{\theta\theta}\right)\right]_{\zeta=1} = 0 \tag{3.21}$$

at the edge of the dome,  $\zeta = 1$  or  $\overline{R} = \Lambda \sqrt{t/\text{Bi}}$ , and

$$2\pi\zeta F_0\mathcal{U}\Lambda^2 = 1 \quad \text{and} \quad F = F_0 \equiv \frac{H_0}{\text{Bi}}$$
 (3.22)

at the vent.

Awkwardly, in the initial-value problem, the vent is located at  $\zeta = \varepsilon = \Lambda^{-1} \sqrt{\text{Bi}/t}$ , which shrinks constantly in time. We can only therefore expect convergence to the selfsimilar solution of (3.18)-(3.21) if that solution becomes independent of  $\varepsilon$  for  $\varepsilon \to 0$ . Alternatively, one can adjust the initial-value problem and apply the inner boundary condition on a vent with radius,  $r = \Lambda \varepsilon \sqrt{t/\text{Bi}}$ , to permit an exact similarity solution.

An analysis of the singular point at the edge  $\zeta = 1$  indicates that

$$\begin{cases} F \\ \mathcal{U} \end{cases} \rightarrow \begin{cases} A(1-\zeta)^{1/3} \\ \frac{1}{2} + \frac{1}{4}(1-\zeta) \end{cases} \quad \text{for} \quad \zeta \to 1,$$
 (3.23)

for some constant A. Rather than employing the inner boundary conditions in (3.22), one can therefore fix A and solve (3.18)-(3.21) as a shooting problem, integrating from a point close to the outer edge into the inner edge at  $\zeta = \varepsilon$ . On arrival, one then determines the value of  $F_0$  corresponding to that choice of A. In practice, this procedure provides solutions only for larger values of  $\varepsilon$ , as the integration becomes relatively stiff for  $\zeta \to 0$ . Instead, one can then switch to solving (3.18)-(3.21) as a boundary-value problem, using the shooting solution as an initial guess. Sample solutions and their behaviour are illustrated in figure 8. Evidently, the bulk of the solution is insensitive to the choices of both  $F_0$  and  $\varepsilon$ .



FIGURE 8. Similarity solutions solved (a)-(b) by shooting for five values of A over the range [1.0112, 1.0465], and (c)-(d) as boundary-value problems for varying  $\varepsilon$  at fixed  $F_0 = 8.57$  (darker blue) and varying  $F_0$  for fixed  $\varepsilon = 0.00625$  (lighter grey). The blue dots in (c)-(d) show the shooting solution used to initiate the boundary-value computations. The red dashed and dotted lines indicate the approximations shown by the legends (with A = 1). In (e) and (f), solutions are continued to still smaller  $\varepsilon$  (as indicated by the stars) using the alternative inner boundary condition  $F(\varepsilon) = -\sqrt{3} \log \varepsilon$ .

Note that  $2\mathcal{T}_{rr} + \mathcal{T}_{\theta\theta} \ll 1$  throughout the interval in  $\zeta$ , leading to the simple approximations,

$$F \sim -\sqrt{3}\log\zeta \qquad \& \qquad \mathcal{U} \sim \frac{1}{2}\zeta^{-\frac{1}{2}}, \tag{3.24}$$

the first of which can be bridged to the limit for  $\zeta \to 1$  by the interpolant,

$$F \sim -[\sqrt{3} - A + A(1 - \zeta)^{-2/3}] \log \zeta.$$
(3.25)

Also, the approximation for  $F(\zeta)$  in (3.24) permits one to construct solutions for arbitrarily small  $\varepsilon$  by employing the alternative boundary condition  $F(\varepsilon) = -\sqrt{3}\log\varepsilon$ , in place of  $F(\varepsilon) = F_0$ . This alternative construction takes advantage of the limiting form of the solution for  $\varepsilon \to 0$ , namely  $F \propto -\log \zeta$  and  $\mathcal{U} \propto -(\zeta \log \zeta)^{-1}$  (see figure 7(f) and Appendix B.1). The logarithmic growth of the fluid depth for  $\zeta \to 0$  corresponds to the piling up of material close to the vent in figure 7.

Finally, turning to the inner flux condition in (3.22), we observe that

$$\Lambda = \left[2\pi\varepsilon F(\varepsilon)\mathcal{U}(\varepsilon)\right]^{-\frac{1}{2}} \to 0.4897 \quad \text{for } \varepsilon \to 0,$$
(3.26)

in view of the numerical solutions in figure 8(c). Thus, despite the corresponding logarithmic divergence of the fluid depth as  $\zeta \to 0$ , the solution does become independent of the vent radius.

## 4. Stability analysis

To study nonaxisymmetrical perturbations to the base flows of  $\S3$ , we set

$$h = H(r,t) + \hat{h}(r,t)e^{im\vartheta}, \quad u = U(r,t) + \hat{u}(r,t)e^{im\vartheta}, \tag{4.1}$$

$$v = \hat{v}(r,t)e^{im\vartheta}, \quad R = \overline{R}(t) + \hat{R}(t)e^{im\vartheta},$$
(4.2)

where m is the angular wavenumber. The amplitudes  $\{\hat{h}, \hat{u}, \hat{v}, \hat{R}\}$  satisfy the linearized equations,

$$0 = \left[H(\hat{h} - 2\hat{\tau}_{\rm rr} - \hat{\tau}_{\theta\theta}) - \hat{h}(2T_{\rm rr} + T_{\theta\theta})\right]_r - \frac{im}{r}H\hat{\tau}_{\rm r\theta} + \frac{H}{r}\left(\hat{\tau}_{\theta\theta} - \hat{\tau}_{\rm rr}\right) + \frac{\hat{h}}{r}\left(T_{\theta\theta} - T_{\rm rr}\right),\tag{4.3}$$

$$0 = \frac{1}{r} \left( r^2 H \hat{\tau}_{\mathrm{r}\theta} \right)_r - im \left[ H (\hat{h} - 2\hat{\tau}_{\theta\theta} - \hat{\tau}_{\mathrm{rr}}) - \hat{h} (2T_{\theta\theta} + T_{\mathrm{rr}}) \right], \tag{4.4}$$

$$\hat{h}_t + \frac{1}{r} [r(U\hat{h} + H\hat{u})]_r + \frac{im}{r} H\hat{v} = 0, \qquad (4.5)$$

where the perturbations to the stress components are given by

$$\hat{\tau}_{\rm rr} = \alpha_{\rm rr}\hat{u}_r + \frac{1}{r}\beta_{\rm rr}(\hat{u} + im\hat{v}), \qquad \hat{\tau}_{\theta\theta} = \alpha_{\theta\theta}\hat{u}_r + \frac{1}{r}\beta_{\theta\theta}(\hat{u} + im\hat{v}), \tag{4.6}$$

$$\hat{\tau}_{\mathbf{r}\theta} = \mu \left[ r \frac{\partial}{\partial r} \left( \frac{\hat{v}}{r} \right) + \frac{im}{r} \hat{u} \right], \qquad (4.7)$$

with

$$\alpha_{\rm rr} = 2\left[\mu + 4\mu' U_r \left(2U_r + \frac{1}{r}U\right)\right], \qquad \beta_{\rm rr} = 8\mu' U_r \left(\frac{2}{r}U + U_r\right), \tag{4.8}$$

$$\alpha_{\theta\theta} = \frac{8}{r} \mu' U \left( 2U_r + \frac{1}{r}U \right), \qquad \beta_{\theta\theta} = 2 \left[ \mu + \frac{4}{r} \mu' U \left( \frac{2}{r}U + U_r \right) \right], \tag{4.9}$$

$$\mu = \frac{1}{\dot{\Gamma}} (\text{Bi} + \dot{\Gamma}^n), \qquad \mu' = -\frac{1}{2\dot{\Gamma}^3} [\text{Bi} + (1-n)\dot{\Gamma}^n].$$
(4.10)

The outer boundary conditions, after a Taylor expansion about the unperturbed edge, are

$$\begin{array}{c}
\hat{R}_{t} = U_{r}\hat{R} + \hat{u} \\
\hat{R}_{t} = -\frac{1}{2}\hat{r}_{rr} - \hat{\tau}_{\theta\theta} - \hat{h}\left(2T_{rr} + T_{\theta\theta}\right) + \left[\frac{1}{2}H^{2} - H(2T_{rr} + T_{\theta\theta})\right]_{r}\hat{R} = 0 \\
\hat{\tau}_{r\theta} - i\hat{m}\hat{R}(T_{\theta\theta} - T_{rr})/\overline{R} = 0
\end{array}\right\} \quad \text{at } r = \overline{R}.$$

$$(4.11)$$

At the vent we demand

$$\hat{u} = \hat{h} = \hat{v} = 0$$
 at  $r = 1.$  (4.12)

These equations can be solved numerically as an initial-value problem. Alternatively, once the base states have converged to self-similar form (power-law or plastic), the corresponding solutions are independent of time once expressed in terms of the similarity coordinates. This permits one to reduce the relevant linear stability analysis to a conventional eigenvalue problem via the coordinate change described in Appendices A.2 and B.2. Before heading down either route, we first consider the early-time limit in which this stability problem simplifies substantially and becomes analytically solvable (cf. Sayag & Worster (2019b)).

Sliding viscoplastic films 15

#### 4.1. Early times, $t \ll 1$

For the early-time solution derived in §3.3, the coefficients in (4.3)-(4.7) become constant to leading order in the small parameter  $\delta$ . Moreover, assuming that  $M = m\delta = O(1)$  and the perturbation amplitudes all remain of comparable order, the leading-order terms in the force-balance equations (4.3)-(4.4) are those with the highest radial and angular derivatives. Thus,

$$0 = (2\hat{\tau}_{\mathrm{rr}} + \hat{\tau}_{\theta\theta})_x + iM\hat{\tau}_{\mathrm{r}\theta} = (2\alpha_{\mathrm{rr}} + \alpha_{\theta\theta})\hat{u}_{xx} + iM(\mu + 2\beta_{\mathrm{rr}} + \beta_{\theta\theta})\hat{v}_x - M^2\mu\hat{u},$$
  

$$0 = (\hat{\tau}_{\mathrm{r}\theta})_x + im(2\hat{\tau}_{\theta\theta} + \hat{\tau}_{\mathrm{rr}}) = \mu\hat{v}_{xx} + iM(\mu + \alpha_{\mathrm{rr}} + 2\alpha_{\theta\theta})\hat{u}_x - M^2(\beta_{\mathrm{rr}} + 2\beta_{\theta\theta})\hat{v},$$
(4.13)

where the coefficients are given by the early-time limits of (4.8)-(4.10) (with  $U/r \rightarrow (2\pi H_0)^{-1}$ ,  $U_r \rightarrow U_{1x}$  and the stress components and  $\dot{\Gamma}$  given by (3.11)-(3.12)). These two relations can be combined into

$$0 = \hat{u}_{xxxx} + \Sigma M^2 \hat{u}_{xx} + \Gamma M^4 \hat{u}, \qquad (4.14)$$

with

$$\Sigma = \frac{3(\beta_{\rm rr}\alpha_{\theta\theta} - \alpha_{\rm rr}\beta_{\theta\theta}) + \mu(2\alpha_{\theta\theta} + \alpha_{\rm rr} + 2\beta_{\rm rr} + \beta_{\theta\theta})}{\mu(2\alpha_{\rm rr} + \alpha_{\theta\theta})}, \quad \Gamma = \frac{2\beta_{\theta\theta} + \beta_{\rm rr}}{2\alpha_{\rm rr} + \alpha_{\theta\theta}}.$$
 (4.15)

Similarly, the boundary conditions become

$$\hat{u} = 0, \quad \hat{v} = 0 \quad \text{at} \quad x = 0,$$
(4.16)

and

$$\frac{(2\alpha_{\rm rr} + \alpha_{\theta\theta})\hat{u}_x + (2\beta_{\rm rr} + \beta_{\theta\theta})iM\hat{v} = 0}{\mu(\hat{v}_x + iM\hat{u}) - iM\hat{R}(T_{\theta\theta} - T_{\rm rr}) = 0}$$
 at  $x = X \equiv (2\pi H_0)^{-1}\hat{t}.$  (4.17)

This system is closed, with the time dependence entering through the motion of the outer edge,  $\hat{R}_{\hat{t}} = \delta[U_{1x}\hat{R} + \hat{u}(X, \hat{t})]$ , and the depth perturbation following separately from (4.5).

We may therefore solve (4.14) subject to (4.16)-(4.17), and then determine the instantaneous growth rate, which we express in terms of the original variables,

$$G(t) = \hat{R}^{-1}\hat{R}_t = U_{1x} + \hat{R}^{-1}\hat{u}(\overline{R}, t).$$
(4.18)

Despite this rewrite, the growth rate on the  $\hat{t}$ -timescale is evidently of  $O(\delta)$ , and so perturbations are predicted to grow far less quickly than the rate of expansion of the base state  $(X = \delta^{-1}(\overline{R} - 1) = (2\pi H_0)^{-1}\hat{t})$ . Also, because depth perturbations decouple from the force balance in this limit (and  $H = H_0$ ), the situation is similar to the two-dimensional extensional flow problem considered by Sayag & Worster (2019b) (the viscoplastic version of which is explored further by Ball *et al.* (2020*a*)). The two problems are not, however, equivalent because, for the sliding shallow current, the radial flow field is not incompressible and the stress state is fully three-dimensional with  $\tau_{\theta\theta} \neq -\tau_{\rm rr}$ . We enjoy the impact of both features on the stability characteristics below.

Irrespective of the rheology, the perturbation amplitude  $\hat{u} \to 0$  for  $MX = m(R - 1) \to 0$ , and so the instantaneous growth rate  $G \to U_{1x} \equiv U_r(1)$  for the lower angular wavenumbers. This term corresponds to the geometrical spreading contribution discussed by Sayag & Worster (2019*b*), which is always equal -1 in their incompressible twodimensional problem. Here, in contrast,  $U_{1x}$  can become positive for sufficiently large  $H_0$  (see figure 9) owing to the thinning of the base state as the fluid leaves the vent when the inflow is relatively deep (*cf.* figure 2). In such cases, the base state is therefore unstable at early times. In the Newtonian limit,  $\Sigma \to -2$  and  $\Gamma \to 1$ , leading to

$$G(t) = \frac{\pi H_0^2 - 2}{8\pi H_0} + \frac{(6 - \pi H_0^2)}{8\pi H_0} \frac{9(MX)^2 - 5\sinh^2(MX)}{9(MX)^2 + 1 + 15\cosh^2(MX)}, \qquad MX \equiv m(\overline{R} - 1).$$
(4.19)

The first term corresponds to  $U_{1x}$  and controls the growth if  $MX \to 0$ ; for  $MX \gg 1$ , on the other hand,  $G \to (\pi H_0^2 - 3)/(6\pi H_0)$ . All wavenumbers become unstable if  $H_0 > \sqrt{3/\pi}$ .

In the plastic limit,  $Bi \gg 1$ , we find  $\Sigma = 1$  and  $\Gamma = \frac{1}{4}$ , giving an instantaneous growth rate,

$$G = -\frac{1}{16\pi H_0} \left[ 1 + 3\cos\left(m\sqrt{2}(\overline{R} - 1)\right) \right].$$
 (4.20)

In this case,  $U_{1x} < 0$  and so instability can only appear when MX is not small. In fact, although G(t) is sometimes positive, there is no net growth, with the average decay rate of  $(8\pi H_0)^{-1}$ . Thus, the spreading shallow plastic current is initially more stable than two-dimensional plastic extensional flow as a result of its different stress state and rate of extension.

Sample instantaneous growth rates away from either of these limits are shown in figure 9. Although G always oscillates in the plastic limit, the instantaneous growth rate eventually reaches a limit  $G_{\infty}$  for  $MX \to \infty$  for any finite Bi, defining a time-independent growth rate that is independent of m. This limit is also plotted in figure 9(c) for several values of n and  $H_0$ .

At early times, the spreading flow is therefore unstable to nonaxisymmetrical perturbations provided the inflow is sufficiently deep and the yield stress is not too large. However, the growth rate is small ( $O(\delta)$  on the timescale at which the relatively narrow annulus expands), and so the fluid is expected to spread beyond the small-time regime before there is much exponential growth. We demonstrate this feature explicitly below in §4.2 on numerical solving of the full initial-value problem.

### 4.2. Numerical results

To proceed beyond the limit of a relatively narrow annulus, we solve the linear stability equations numerically beginning with the initial conditions,  $\hat{R}(0) = 1$  and  $\hat{h}(r,0) = 0$ . Figure 10 displays solutions for Newtonian fluid with three values of m and  $H_0$ . For the entrance depths chosen ( $H_0 = 1$ , 3 and 5), the stability theory for early times predicts exponentially growing instabilities at early times ( $\pi H_0^2 > 2$ ). For wavenumbers of m = 2and 10, the instantaneous growth rate  $G = G_0 = U_{1x}$  for  $MX \ll 1$  characterizes the amplification until the base state has spread beyond a narrow annulus. The highest wavenumber of m = 100, however, is sufficiently large to trigger a transition towards the growth rate  $G = G_{\infty}$  applying in the limit  $MX \gg 1$ .

Once the fluid has spread beyond the early-time regime, instability gradually switches off, giving way to a late-time algebraic decay relative to the expansion of the base state (the perturbations actually continue to grow algebraically in time in this latter phase, but with a power of time that is less than that of  $\overline{R}(t) \sim t$ ). This decay becomes independent of the entrance depth  $H_0$  at the latest times, with a weak dependence on m. During this evolution, the linear solutions do not inherit a great deal of spatial structure, although they become more localized to the outer edge at later times and for higher wavenumber (figure 10(b)).

The late-time power-law decay corresponds to the convergence of the perturbations towards a self-similar spatial structure equivalent to that of the base state (§3.1), in which  $\zeta = r/\overline{R}$  and  $[\hat{u}(r,t), \hat{v}(r,t), \hat{h}(r,t)] = \hat{u}(\overline{R},t)[\check{\mathcal{U}}(\zeta), \check{\mathcal{V}}(\zeta), \check{F}(\zeta)/\overline{R}]$ . Figure 10(c)-(e)

Sliding viscoplastic films



FIGURE 9. Instantaneous growth rates G(t) as function of Bi and  $MX = m(\overline{R} - 1)$  for (a)  $H_0 = \frac{2}{3}$  and (b)  $H_0 = \frac{4}{3}$ , with n = 1. The blue curves highlight the contour G = 0. In (c) and (d), we plot the limiting growth rates  $G_0 = U_{1x}$  and  $G_\infty = \lim_{M \to \infty} (G)$  against Bi for n = 0.25, 0.4, 0.6, 0.8 and 1, with the values of  $H_0$  indicated.

illustrates this structure over longer times for the case with  $H_0 = 1$  and m = 2. Further details of this limit are given in Appendix A.2, where the transformation to the similarity variables facilities a standard normal-mode-style stability analysis. That analysis predicts that the Newtonian problem is stable; the damping rates and perturbation amplitudes are indicated in figure 10 and compare well with the results from numerical solution of the initial-value problem. Note the increasingly abrupt rise in  $\hat{h}(r, t)$  near the outer edge, emerging because the base state develops an infinite slope in the self-similar limit.

Figure 11 shows an analogous set of examples with a yield stress. In this case, the expansion of the basic spreading flow out-competes the perturbations in the early-time limit (with  $\hat{R}/\bar{R}$  decaying), but modes begin to grow relative to the base state at later times. The lowest yield-stress case for Bi = 0.1 displays little overall amplification of the linear modes, with the lowest angular wavenumber remaining strongest at the termination of the computation. For Bi = 1, the modes (with m = 2 to 16) grow at comparable late-time rates. With Bi = 10, however, the higher wavenumber modes amplify quicker and substantially. Unlike the Newtonian case, the perturbations do not become confined to the outer edge as the fluid expands, but retain significant amplitudes throughout the fluid, displaying spatial oscillations that narrow with increasing angular wavenumber (figure 11(b)), a feature mirroring results in the two-dimensional problem of (Sayag & Worster 2019b). For the higher values of m, the perturbation to the edge  $\hat{R}(t)$  also begins to oscillate in time with a frequency that increases with m.

As discussed in Appendix B.2, stronger instability at higher m, oscillatory growth and persistent spatial oscillations also feature for the linear modes in the self-similar plastic limit. The analysis there, in fact, predicts a (power-law) growth rate that increases as  $m^2$ , implying a rather singular limit to the stability problem. The enhanced amplification



FIGURE 10. Solutions of the initial-value problem for linear perturbations to Newtonian spreading flow (n = 1, Bi = 0), showing (a) time series of the perturbed radius scaled by the base state radius for the values of  $H_0$  and m indicated, and (b) the perturbed radial velocity  $\hat{u}$  for  $H_0 = 1$  at the times indicated (successively offset and with the colour coding representing m as in (a)). The inset to (a) shows the early-time behaviour of  $\hat{R}(t)$  along with the asymptotic predictions of §4.1 (dashed); the dotted lines show the power laws  $t^{-0.8}$  (top),  $t^{-0.81}$  and  $t^{-0.76}$  (bottom) predicted by the analysis in Appendix A.2. In (c)–(e), with m = 2 and  $H_0 = 1$ , the solutions for  $\hat{u}(r, t)$ ,  $\hat{v}(r, t)$  and  $\hat{h}(r, t)$  are scaled and plotted against  $r/\overline{R}(t)$  every 50 time units upto the extended time of  $t = 10^3$ ; the dashed lines show the self-similar solutions from Appendix A.2, taking  $\varepsilon = 0.006$ .



FIGURE 11. Solutions of the initial-value problem for linear perturbations to Bingham spreading flow (n = 1, Bi > 0) with  $H_0 = 1$ . (a) Time series of the perturbed radius scaled by the base state radius,  $\hat{R}/\overline{R}$ , for the values of m indicated; the solid lines show results for Bi = 1, the dotted lines for Bi = 0.1 and the dot-dashed lines for Bi = 10 (computations are terminated when  $|\hat{R}|/\overline{R} = 10^6$ ). The black dashed lines show the growth expected from §B.2, based on the final value of  $\varepsilon = \overline{R}^{-1}$ . The inset shows the early-time behaviour of  $\hat{R}(t)$  along with the approximation  $e^{U_{1x}t}$  (dashed). (b) Snapshots of  $(\hat{u}, \hat{v}, (2\pi)^{-1}\hat{h})/\text{Max}(\hat{u})$  at t = 100 for Bi = 1 (solid, dashed and dotted, respectively, with the colour coding representing m as in (a)). (c) The final snapshots of  $\hat{v}$  for Bi = 10. The dots show the corresponding self-similar solutions of §B.2; for the complex modes with m = 8 and 16, a constant phase is chosen arbitrarily.

at larger Bi and m seen in figure 11 evidently points to the emergence of this divergent behaviour. A quantitative comparison of the numerical results in this figure with the self-similar solutions is not possible, however, because these Bingham computations have yet to converge to self-similar form. Moreover, since the vent radius is not fixed but expanding in the similarity solutions, such a comparison only makes sense if results are insensitive to the position and conditions at the inner edge, which is far from the case in



FIGURE 12. Solutions of the initial-value problem for linear perturbations for power-law fluid (Bi = 0) for the values of n indicated and  $H_0 = 2$ . In the main panels, perturbed radius scaled by the base state radius is plotted for (a) m = 4 and (b) m = 1. The dotted lines indicate the power laws  $t^{\lambda_r}$  predicted for the self-similar solutions in §B.2. The insets show the final snapshots of  $\hat{v}$ .

the plastic limit. Despite this, if we take the value of  $\varepsilon = \overline{R}^{-1}$  implied at the end of the computations for Bi = 10 (which is the closest to the plastic limit) and compute  $\lambda$  using the analysis in §B.2, we emerge with a qualitative guide to the instantaneous growth rate (see the dashed lines in the main panel of figure 11(a)). Similarly, the corresponding self-similar solutions broadly reproduce the spatial structure of the final snapshots (figure 11(c)).

The addition of a yield stress therefore significantly destabilizes the spreading, shallow current at late times. The situation is somewhat similar for a power-law fluid (Bi = 0), with a decrease of n playing the same role as an increase in Bi. Figure 12 presents results for m = 4 and 1, with a variety of values for n. For these two modes, the linear stability analysis of the self-similar solutions in §A.2 predicts instability for n slightly less than 0.2 and 0.55, respectively, with the m = 4 mode having a finite frequency. These predictions are again broadly reproduced in the numerical computations. Moreover, unlike in the plastic limit, a more detailed comparison of the mode shapes shows satisfying agreement (see §B.2), primarily because the perturbations decay more strongly towards the inner boundary, rendering the solutions less sensitive to the inflow conditions. The growth rates also remain bounded, at least with finite n.

## 5. Discussion

In this paper we have investigated the stability of sliding viscoplastic films. This work is motivated by experiments in which a dramatic non-axisymmetrical instability appears in radially expanding films of Xanthan gum solution (Sayag *et al.* 2012; Sayag & Worster 2019*a*) and Carbopol suspensions (figure 1; Ball *et al.* (2020*b*)). Sayag & Worster (2019*b*) rationalized these observations in terms of an instability of two-dimensional, radial extensional flow of a power-law fluid. However, this instability may be weak under typical experimental conditions (Ball *et al.* 2020*a*) and different for base flows that thin as they spread and possess three-dimensional stress states. In view of this, and to provide a theoretical discussion that is also relevant for yield-stress fluids, we considered in this paper the instability of spreading thinning films of Herschel-Bulkley fluids.

As a first step, we constructed axisymmetrical spreading states. Without a yield stress, power-law fluids develop a steady flow structure near the source but evolve to a self-similar form further away, as discussed by Pegler & Worster (2012) for Newtonian fluid. The addition of a yield stress eliminates such states, however, because the continued fall of the rate of extension as the fluid spreads inexorably promotes the importance of the yield stress in comparison to the viscous stresses. Instead, the current reaches a different self-similar regime corresponding to a plastic limit dominated by the yield stress; *i.e.* flow dictated by perfectly plastic deformation (Prager & Hodge 1951).

A linear stability analysis of the base states demonstrates the instability of Sayag & Worster (2019b) and Sayag (2019) still operates for a spreading thinning film, although the details are somewhat different. The dynamics breaks down into an early-time phase wherein the spreading current remains a relatively narrow annulus, and a late-time, self-similar regime. In the early time phase, the thinning of the base flow can drive linear instability provided the yield stress is not too large, although amplification is always weak, with perturbations growing more slowly than the expansion of the base state. Currents with relatively strong yield stresses are linearly stable at early times, in contrast to the viscoplastic version of Sayag & Worster's two-dimensional problem (Ball *et al.* 2020*a*).

In the late-time, self-similar regime, non-axisymmetrical perturbations subside in Newtonian fluids, in line with experimental observations (Pegler & Worster 2012; Sayag & Worster 2019*a*). However, with either a yield stress or a sufficiently strongly shearthinning viscosity, non-axisymmetrical perturbations begin to grow relative to the expansion of the base state. In the plastic limit, to which the fluid inevitably approaches whenever there is a yield stress, the instability becomes especially pronounced, the linear stability analysis predicting singular behaviour. The viscoplastic, spreading and thinning current therefore appears to be rather more unstable than its two-dimensional analogue, but only over late times when the fluid has expanded over distances well exceeding the initial radius. Of course, it is also true that our exploration has been limited to a linear analysis and it is conceivable that nonlinearity plays a more intrusive role.

Awkwardly, in experiments like that shown in figure 1, the nonaxisymmetrical patterns develop immediately, as soon as the fluid leaves the launch stage and begins to thin above the ambient bath. There is also evidence from both the free-surface experiments and from other experiments in Hele-Shaw cells that an extensional flow instability cannot be the complete story (Ball *et al.* 2020a,b): in order to develop extensional flow without significant shear across the spreading film, one must avoid any friction with the underlying surface. This was achieved by Sayag *et al.* and in the Carbopol experiment of figure 1 by floating the complex fluid over a bath of water. Particularly with the Carbopol experiment, however, the water bath is relatively shallow, and there is little sign that much water remains underneath the Carbopol a short distance from the launch

stage. In experiments in which Carbopol was pumped into water-filled Hele-Shaw cells, there was similarly little evidence for relatively thick residual wall layers of water. For both experiments it is likely that there is therefore significant shear across the film. Despite this, fingering patterns still develop, and appear much like the Xanthan gum experiments of Sayag *et al.*, which use much deeper water baths. Crucially, if a different, immiscible liquid with comparable viscosity (such as paraffin or mineral oil) is used for the ambient fluid the experiments are substantially different, with non-axisymmetric patterns potentially eliminated entirely. Thus, interfacial interaction with the bath appears to play an important role. In fact, the Hele-Shaw experiments (Ball *et al.* 2020*a*) suggest that a completely different mechanism might be at play: the fracture under tension of the material, exacerbated by the presence of water. How the extensional flow instability competes or cooperates with fracture to create the finger pattern remains unclear.

## Acknowledgements

We thank Mark Martinez, Stephen Morris, Roiy Sayag and Grae Worster for helpful discussions.

## **Declaration of Interests**

The authors report no conflict of interest.

## Appendix A. Self-similar solutions for Bi = 0

A.1. Base states

We set

$$\zeta = \frac{r}{\Lambda t^{\frac{1}{2}(1+n)}}, \quad F(\zeta) = t^n H, \quad \mathcal{U}(\zeta) = \Lambda^{-1} t^{\frac{1}{2}(1-n)} U.$$
(A1)

The equations for the base state become

$$\mathcal{U}_{\zeta} = \frac{F}{8\mathcal{M}} - \frac{Z}{4\mathcal{M}F} - \frac{\mathcal{U}}{2\zeta}, \qquad F_{\zeta} = \frac{(n - \zeta^{-1}\mathcal{U} - \mathcal{U}_{\zeta})F}{\mathcal{U} - \frac{1}{2}(n+1)\zeta}, \qquad Z_{\zeta} = 2\mathcal{M}F\left(\frac{\mathcal{U}}{\zeta}\right)_{\zeta}, \quad (A\,2)$$

where  $Z(\zeta) \equiv t^{2n} \left[\frac{1}{2}H^2 - H(2T_{\rm rr} + T_{\theta\theta})\right]$  and

$$\mathcal{M}(\zeta) \equiv \left(2\sqrt{\mathcal{U}_{\zeta}^{2} + \zeta^{-1}\mathcal{U}\mathcal{U}_{\zeta} + \zeta^{-2}\mathcal{U}^{2}}\right)^{n-1}.$$
 (A 3)

The outer boundary conditions are

$$\mathcal{U} \to \frac{1}{2}(1+n), Z \to 0, \text{ for } \zeta \to 1,$$
 (A4)

which leaves free the amplitude of a singular solution of the form  $(1-\zeta)^{(3n-1)/4}$  for  $n > \frac{1}{3}$ (in which case  $F \to 2\mathcal{M}(3n-1)$ ) or  $(1-\zeta)^{(1-3n)/3(n+1)}$  for  $n < \frac{1}{3}$  (and  $F \to 0$ ). The solution is therefore fully specified by the inner boundary condition, which corresponds to the match to the steady profile in §3.1:

$$F \to \tilde{H}_0(\Lambda\zeta)^{-2n/(n+1)}, \quad \mathcal{U} \to \frac{\zeta(\Lambda\zeta)^{-2/(n+1)}}{2\pi\tilde{H}_0},$$
 (A 5)

and

$$Z \to \frac{1}{2}F^2 - 2^n(3n-1)(1+3n^2)^{(n-1)/2}(1+n)^{-n}F(\mathcal{U}/\zeta)^n.$$
 (A6)

The last relation proves convenient to impose the inner boundary condition at a finite position,  $\zeta = \varepsilon$ , with  $\varepsilon$  sufficiently small to ensure that its value has little impact on the solution. Finally, the inner flux condition demands

$$1 = 2\pi r H U \to \Lambda^2 \zeta F \mathcal{U} \tag{A7}$$

at  $\zeta = \varepsilon$ , which determines  $\Lambda$ , and therefore the position of the outer edge,  $\overline{R} \equiv \Lambda t^{\frac{1}{2}(1+n)}$ . For example, we find  $\Lambda = 0.173$  for n = 1 and  $\Lambda = 0.328$  for n = 0.4. The corresponding self-similar solutions are plotted in figure 4 and compared with the (suitably scaled) solutions of the initial-value problems in figures 2 and 3 (including factors of the powers of  $\zeta$  required to suppress divergence for  $\zeta \to 0$ ).

#### A.2. Linear stability

To explore the linear stability, we set

$$h = t^{-n} [F(\zeta) + t^{\lambda} e^{im\vartheta} \check{F}(\zeta)], \quad u = \Lambda t^{-\frac{1}{2}(1-n)} [\mathcal{U}(\zeta) + t^{\lambda} e^{im\vartheta} \check{\mathcal{U}}(\zeta)], \quad (A8)$$

$$v = im\Lambda t^{\lambda - \frac{1}{2}(1-n)} e^{im\vartheta} \Psi(\zeta), \quad R = \Lambda t^{\frac{1}{2}(1+n)} [1 + t^{\lambda} e^{im\vartheta} \check{R}], \tag{A9}$$

$$\check{F} = \frac{\check{X} - \zeta F \check{\mathcal{U}}}{\zeta [\mathcal{U} - \frac{1}{2}(n+1)\zeta]}, \qquad \check{Y} = \zeta^2 \mathcal{M} F\left(\frac{\check{\mathcal{U}} - \Psi}{\zeta} + \Psi_\zeta\right), \tag{A 10}$$

and

$$t^{\lambda-2n} e^{im\vartheta} \check{Z}(\zeta) = H(\hat{h} - 2\hat{\tau}_{\rm rr} - \hat{\tau}_{\theta\theta}) - \hat{h}(2T_{\rm rr} + T_{\theta\theta}). \tag{A11}$$

The linear equations can then be written as

$$\check{\mathcal{U}}_{\zeta} = \frac{[\zeta F - 2\mathcal{M}(2\zeta \mathcal{U}_{\zeta} + \mathcal{U})]\check{F} - \zeta \check{Z} - F(2\tilde{\beta}_{\mathrm{rr}} + \tilde{\beta}_{\theta\theta})(\check{\mathcal{U}} - m^{2}\Psi)}{(2\tilde{\alpha}_{\mathrm{rr}} + \tilde{\alpha}_{\theta\theta})\zeta F},\tag{A 12}$$

$$\check{X}_{\zeta} = m^2 F \Psi - \zeta (1+\lambda) \check{F}, \tag{A13}$$

$$\check{Z}_{\zeta} = \frac{2\mathcal{M}}{\zeta^2} (\zeta \mathcal{U}_{\zeta} - \mathcal{U})\check{F} + \frac{F}{\zeta^2} [(\tilde{\alpha}_{\rm rr} - \tilde{\alpha}_{\theta\theta})\zeta \check{\mathcal{U}}_{\zeta} + (\tilde{\beta}_{\rm rr} - \tilde{\beta}_{\theta\theta})(\check{\mathcal{U}} - m^2 \Psi)] - \frac{m^2}{\zeta^3}\check{Y}, \quad (A\,14)$$

$$\Psi_{\zeta} = \frac{\Psi - \mathcal{U}}{\zeta} + \frac{Y}{\zeta^2 \mathcal{M} F},\tag{A15}$$

$$\check{Y}_{\zeta} = [\zeta F - 2\mathcal{M}(2\mathcal{U} + \zeta\mathcal{U}_{\zeta})]\check{F} - \zeta F(2\tilde{\alpha}_{\theta\theta} + \tilde{\alpha}_{\mathrm{rr}})\check{\mathcal{U}}_{\zeta} - F(2\tilde{\beta}_{\theta\theta} + \tilde{\beta}_{\mathrm{rr}})(\check{\mathcal{U}} - m^{2}\Psi), \quad (A\,16)$$

where  $(\tilde{\alpha}_{\rm rr}, \tilde{\alpha}_{\theta\theta}, \tilde{\beta}_{\rm rr}, \tilde{\beta}_{\theta\theta}) = t^{n-1}(\alpha_{\rm rr}, \alpha_{\theta\theta}, \beta_{\rm rr}, \beta_{\theta\theta})$ . At the unperturbed outer radius  $\zeta = 1$ , we impose

$$\check{\mathcal{U}} = [\lambda + \frac{1}{2}(n+1) - \mathcal{U}_{\zeta}]\check{R}, \quad \check{Z} + Z_{\zeta}\check{R} = 0, \quad \check{Y} - 2\mathcal{M}F(\mathcal{U} - \mathcal{U}_{\zeta})\check{R} = 0.$$
(A 17)

and set  $\Psi(\varepsilon) = \dot{X}(\varepsilon) = \dot{\mathcal{U}}(\varepsilon) = 0$  to ensure that the solution does not diverge at the inner boundary (although the solution appears to be insensitive to these conditions as long as it remains regular for  $\zeta \to 0$  and n and m are not too small).

The numerical solution of this linear problem furnishes only stable eigenvalues with  $\lambda_r \equiv \operatorname{Re}(\lambda) < 0$  for the Newtonian problem (n = 1). However, a reduction in n increases  $\lambda_r$  and eventually unstable modes appear; see figure 13. The m = 1 mode becomes unstable for n slightly below 0.6 (and remains real); instabilities with higher wavenumber require  $n < \frac{1}{3}$ , and are complex with frequencies  $\lambda_i \equiv \operatorname{Im}(\lambda) \neq 0$ . Solutions for the perturbation amplitudes are compared with numerical solutions of the Newtonian initial-value problem in figure 10, and figure 14 displays a selection of solutions for  $\Psi(\zeta)$  for various values of n,  $\varepsilon$  and m. The cases with different  $\varepsilon$  are hard to distinguish in figure



FIGURE 13. Eigenmodes of the linear stability problem for self-similar solutions with Bi = 0, showing (a)  $\lambda_r$  and against m for n = [0.1, 0.15, 0.2, 0.4, ..., 1] and  $\lambda_i$  against m for n = [0.1, 0.15, 0.2], and (b)  $\lambda_r$  against n for m = 1. In both panels, data for  $\varepsilon = 10^{-3}$  (solid), 0.01, 0.05 and 0.1 (all dashed) are shown.



FIGURE 14. Eigenfunctions  $\Psi$  for (a) n = 1, (b) n = 0.4 and (c) n = 0.1, with  $\varepsilon = 0.1$  (dashed) and 0.01 (solid). Modes with m = 1, 4 and 10 are plotted (as indicated by color). The dash-dot lines show more m = 1 solutions for  $\varepsilon = 10^{-3}$ . In (c), the real parts of the complex modes with m > 1 are plotted. The dots show numerical solutions of the initial-value problem at  $t \approx 300$  for a selection of the cases (m = 10 in (a); m = 1 and 4 in (b); m = 4 in (c)).

14, except at smaller m and n where the solutions become sensitive to  $\varepsilon$  because the corresponding mode shapes fail to decay towards the inner boundary and begin to pile up against it. Also, the flattening out of the growth-rate curves in figure 13(a) can be rationalized by a WKB-style analysis in the limit  $m \gg 1$ , where the solutions decay rapidly away from the outer boundary and depend on the spatial coordinate  $m(1 - \zeta)$ . The analysis is complicated by the presence of the singular point at  $\zeta = 1$ , and the fact that its nature switches for  $n = \frac{1}{3}$ , but otherwise predicts that  $\lambda$  becomes independent of m.

## Appendix B. Plastic self-similar solutions

B.1. The limit  $\varepsilon \to 0$ 

Writing

$$Z = F(\frac{1}{2}F - 2C), \qquad 2\mathcal{U}_{\zeta} + \frac{\mathcal{U}}{\zeta} = \dot{\gamma}C(\zeta), \qquad \sqrt{3}\frac{\mathcal{U}}{\zeta} = \dot{\gamma}S(\zeta) \qquad \& \qquad 1 = C^2 + S^2, \tag{B1}$$

the equations for the axisymmetrical similarity solution read

$$F_{\zeta} = \frac{F\mathcal{U}(\sqrt{3}C+S)}{\zeta S(\zeta-2\mathcal{U})}, \qquad \mathcal{U}_{\zeta} = \frac{\mathcal{U}}{2S\zeta}\left(\sqrt{3}C-S\right), \qquad Z_{\zeta} = \frac{F}{\zeta}\left(C-\sqrt{3}S\right). \tag{B2}$$

For  $\zeta \to 0$ , the solution for F diverges logarithmically, whereas |C| is bounded by unity. Thus,  $Z \to F^2/2$ . The first and last equations in (B 2) can then only be consistent if  $C \to -S/\sqrt{3}$ , or  $(C, S) \to \frac{1}{2}(-1, \sqrt{3})$ . This further implies that  $F \sim -2 \log \zeta$  and  $\mathcal{U} \propto \zeta^{-1}$ ; logarithmic corrections obscure this limit in the numerical solutions. In particular, we note that  $C \sim -S/\sqrt{3}+2/F$ , retaining the next correction. Thence,  $\mathcal{U}_{\zeta} \sim -(1-2/F)\mathcal{U}/\zeta$ , which furnishes  $\mathcal{U} \sim -c(\zeta \log \zeta)^{-1}$ , for some constant c, as seen in figure 8(f).

We may also observe from (B 2) that  $(\zeta F \mathcal{U})_{\zeta} \sim O(\zeta)$  for  $\zeta \to 0$ . It follows that

$$[\zeta F \mathcal{U}]_{\zeta \to 0} = \int_0^1 F(\zeta) \zeta d\zeta \approx 0.664, \tag{B3}$$

using the computations in figure 8(c), which simply corresponds to mass conservation for the self-similar solution. This result leads to the limit in (3.26).

#### B.2. Linear stability

For the perturbations to the similarity solution we set

$$h = \operatorname{Bi}[F(\zeta) + t^{\lambda} e^{im\vartheta} \check{F}(\zeta)], \quad u = \Lambda t^{-\frac{1}{2}} \operatorname{Bi}^{-\frac{1}{2}} [\mathcal{U}(\zeta) + t^{\lambda} e^{im\vartheta} \check{\mathcal{U}}(\zeta)], \tag{B4}$$

$$v = im\Lambda t^{\lambda - \frac{1}{2}} \operatorname{Bi}^{-\frac{1}{2}} e^{im\vartheta} \Psi(\zeta), \quad R = \Lambda t^{\frac{1}{2}} \operatorname{Bi}^{-\frac{1}{2}} [1 + t^{\lambda} e^{im\vartheta} \check{R}].$$
(B5)

Now we define  $\check{Y}, \check{Z}$  and  $\check{X}$  through the relations

$$\check{Y} = \frac{\zeta^2 F}{\dot{\Gamma}} \left( \frac{\check{\mathcal{U}} - \Psi}{\zeta} + \Psi_{\zeta} \right), \qquad \check{Z} = (F - 2C)\check{F} - F(2\check{\tau}_{\rm rr} + \check{\tau}_{\theta\theta}), \tag{B6}$$

$$\check{F} = \frac{\check{X} - \zeta F \check{\mathcal{U}}}{\zeta (\mathcal{U} - \frac{1}{2}\zeta)} \qquad \& \qquad \dot{\Gamma} = 2\sqrt{\mathcal{U}_{\zeta}^2 + \frac{\mathcal{U}\mathcal{U}_{\zeta}}{\zeta} + \frac{\mathcal{U}^2}{\zeta^2}} \equiv \frac{\sqrt{3}\mathcal{U}}{\zeta S}, \tag{B7}$$

where the normal stress perturbations are

$$(\check{\tau}_{\rm rr}, \check{\tau}_{\theta\theta}) = \frac{1}{2F} [(F - 2C)\check{F} - \check{Z}] \left( 1 + \frac{C}{S\sqrt{3}}, -\frac{2C}{S\sqrt{3}} \right).$$
 (B8)

The linearized equations for the perturbations can then be written as

$$\check{\mathcal{U}}_{\zeta} = \frac{\zeta \check{\Gamma}[(F-2C)\check{F}-\check{Z}] - 2FS(S-\sqrt{3}C)(\check{\mathcal{U}}-m^{2}\Psi)}{4\zeta FS^{2}},\tag{B9}$$

$$\check{X}_{\zeta} = m^2 F \Psi - \zeta (1+\lambda) \check{F},\tag{B10}$$

$$\check{Z}_{\zeta} = \frac{1}{\zeta} (C - \sqrt{3}S)\check{F} + \frac{1}{2\zeta S} (S + \sqrt{3}C) [(F - 2C)\check{F} - \check{Z}] - \frac{m^2}{\zeta^3} \check{Y}, \tag{B11}$$

$$\Psi_{\zeta} = \frac{\Psi - \check{\mathcal{U}}}{\zeta} + \frac{\dot{\Gamma}\check{Y}}{\zeta^2 F},\tag{B12}$$

$$\check{Y}_{\zeta} = \zeta (F - C - \sqrt{3}S)\check{F} - \frac{\zeta}{2S} (S - C\sqrt{3}) [(F - 2C)\check{F} - \check{Z}].$$
(B13)

The boundary conditions are, at  $\zeta = \varepsilon$ ,

$$\Psi = \check{F} = \check{\mathcal{U}} = 0 \tag{B14}$$

and, near the unperturbed outer radius  $\zeta = 1$ ,

$$\check{\mathcal{U}} \sim (\lambda + \frac{3}{4})\check{R}, \quad \check{Z} \sim \sqrt{3}F\check{R}, \quad \check{Y} \sim \sqrt{3}F\check{R}.$$
(B 15)

The singular point at the edge again impacts the linear stability problem: in order to shift the outer boundary, the perturbation to the depth at  $\zeta = 1$  must diverge according to  $\check{F} \sim$  $-F_{\zeta}\check{R}$ . The dependent variables above, however, avoid any divergences. Nevertheless, one must be careful to exclude solutions to (B 9)-(B 13) that diverge more strongly than implied by (B 15). Indeed, we find numerical evidence for infinitely many solutions with Real( $\lambda$ ) close to -1 that possess unphysical behaviour at the edge. Eliminating these leaves a finite set of physically relevant modes that can be unstable.

Numerical solutions to the linear stability problem are shown in figures 15–16. The first figure displays a pair of unstable modes that arises for smaller angular wavenumbers m for a base state with  $\varepsilon = 0.05$ . With increasing m, the eigenvalues of these modes pass through a curious sequence of interactions wherein the pair either splits into distinct, real values or collide into a complex conjugate pair. Overall, the growth rate  $\lambda_r$  increases with  $m^2$ , whereas the frequency of the conjugate pair scales with m. As displayed by the eigenfunctions for  $\mathcal{U}(\zeta)$  included in the plot, the modes acquire more spatial oscillations as m increases. At higher m, further unstable modes appear, but at the values of m plotted, no other growing eigenvalues were found. Some additional analytical progress is possible in the high-wavenumber limit using WKB theory: the eigenfunctions acquire an oscillatory structure given by  $\exp(\frac{1}{2}im\sqrt{2}\log\zeta)$ , with a more slowly varying amplitude that is roughly independent of m.

Growth rates for varying domain sizes (*i.e.*  $\varepsilon$ ) are shown in figure 16. Notably, the growth rates appear to diverge in the limit  $\varepsilon \to 0$ , with  $\lambda_r = O(\varepsilon^{-a}m^2)$  and 1.5 < a < 2. Conversely, the instability is much reduced in the limit of a relatively narrow annulus,  $\varepsilon \to 1$ , where further asymptotic analysis demonstrates that  $\lambda_r \approx (1-\varepsilon)^2 m^2/12$ . In the plastic limit, the instability is therefore markedly different from the two-dimensional instability explored by Sayag & Worster (2019b). For that problem, the instantaneous growth rate is maximized for m = 1 and all the higher angular modes pass repeatedly through phases of stability and instability as the fluid expands (Ball *et al.* 2020*a*). Here, the instability grows monotonically with the expansion of the dome and the shorter-wavelength modes amplify fastest, at least until angular wavelength becomes comparable to the thickness of the dome and the shallow-layer approximation breaks down. Consequently, the extensional flow instability appears to be stronger for a thinning expanding dome.



FIGURE 15. Eigenvalues  $\lambda = \lambda_r + i\lambda_i$  against m for a base state with A = 1.03 ( $F_0 = 5.86$ ) and  $\varepsilon = 0.05$ . The eigenvalues are computed treating m as an real number; the solution with integer m are shown as circles, coloured according to whether they are real (blue and red, with the former having a  $\lambda$  greater than that of the latter) or complex (green). The insets show the mode shapes for  $\tilde{\mathcal{U}}(\zeta)$ .



FIGURE 16. Eigenvalues  $\lambda = \lambda_r + i\lambda_i$  against *m* for the values of  $\varepsilon$  indicated (with A = 1.029112 for  $\varepsilon = 0.015$ , A = 1.03 for  $\varepsilon = 0.05$ , and A = 1 for the cases with larger  $\varepsilon$ ). The dashed lines show the linear and quadratic curve of figure 15.

#### REFERENCES

- BALL, THOMASINA V, BALMFORTH, NEIL J & DUFRESNE, A 2020a Viscoplastic fingers and fractures in a hele-shaw cell. Journal of non-Newtonian fluid mechanics subm. .
- BALL, THOMASINA V, BALMFORTH, NEIL J & MORRIS, S 2020b Fracture patterns in viscoplastic gravity currents? In preparation .

- BALMFORTH, N. J. 2018 Viscoplastic asymptotics and other techniques. Viscoplastic Fluids: From Theory to Application, CISM. Springer.
- BALMFORTH, N. J., FRIGAARD, I. & OVARLEZ, G. 2014 Yielding to stress: Recent developments in viscoplastic fluid mechanics. Ann. Rev. Fluid Mechanics 46, 121–146.
- BARNES, HOWARD A 1995 A review of the slip (wall depletion) of polymer solutions, emulsions and particle suspensions in viscometers: its cause, character, and cure. *Journal of Non-Newtonian Fluid Mechanics* 56 (3), 221–251.
- CRASTER, RV & MATAR, OK 2009 Dynamics and stability of thin liquid films. Reviews of modern physics 81 (3), 1131.
- ENGLAND, PHILIP & MCKENZIE, DAN 1982 A thin viscous sheet model for continental deformation. *Geophysical Journal International* **70** (2), 295–321.
- ENGLAND, PHILIP & MCKENZIE, DAN 1983 Correction to: A thin viscous sheet model for continental deformation. *Geophysical Journal International* 73 (2), 523–532.
- KOCH, DOROTHY M & KOCH, DONALD L 1995 Numerical and theoretical solutions for a drop spreading below a free fluid surface. *Journal of Fluid Mechanics* 287, 251–278.
- LIU, Y, BALMFORTH, N J & HORMOZI, S 2018 Axisymmetric viscoplastic dambreaks and the slump test. Journal of Non-Newtonian Fluid Mechanics 258, 45–57.
- LUU, LI-HUA & FORTERRE, YOEL 2009 Drop impact of yield-stress fluids. Journal of Fluid Mechanics 632, 301–327.
- LUU, LI-HUA & FORTERRE, YOËL 2013 Giant drag reduction in complex fluid drops on rough hydrophobic surfaces. *Physical review letters* **110** (18), 184501.
- MACAYEAL, DOUGLAS R 1989 Large-scale ice flow over a viscous basal sediment: Theory and application to ice stream b, antarctica. *Journal of Geophysical Research: Solid Earth* **94** (B4), 4071–4087.
- MACAYEAL, DOUGLAS R & BARCILON, VICTOR 1988 Ice-shelf response to ice-stream discharge fluctuations: I. unconfined ice tongues. *Journal of Glaciology* **34** (116), 121–127.
- MASCIA, SALVATORE, PATEL, MJ, ROUGH, SL, MARTIN, PJ & WILSON, D IAN 2006 Liquid phase migration in the extrusion and squeezing of microcrystalline cellulose pastes. *European journal of pharmaceutical sciences* **29** (1), 22–34.
- ORON, ALEXANDER, DAVIS, STEPHEN H & BANKOFF, S GEORGE 1997 Long-scale evolution of thin liquid films. *Reviews of modern physics* **69** (3), 931.
- PEGLER, SAMUEL S, LISTER, JOHN R & WORSTER, M GRAE 2012 Release of a viscous powerlaw fluid over an inviscid ocean. *Journal of fluid mechanics* **700**, 63–76.
- PEGLER, SAMUEL S & WORSTER, M GRAE 2012 Dynamics of a viscous layer flowing radially over an inviscid ocean. *Journal of fluid mechanics* **696**, 152–174.
- DI PIETRO, ND & COX, RG 1979 The spreading of a very viscous liquid on a quiescent water surface. The Quarterly Journal of Mechanics and Applied Mathematics 32 (4), 355–381.
- PRAGER, W. & HODGE, P. G. 1951 Theory of perfectly plastic solids. Wiley.
- ROUSSEL, NICOLAS, LANOS, CHRISTOPHE & TOUTOU, ZAHIA 2006 Identification of bingham fluid flow parameters using a simple squeeze test. Journal of non-newtonian fluid mechanics 135 (1), 1–7.
- SAYAG, ROIY 2019 Rifting of extensional flows on a sphere. *Physical Review Letters* **123** (21), 214502.
- SAYAG, ROIY, PEGLER, SAMUEL S & WORSTER, M GRAE 2012 Floating extensional flows. Physics of Fluids 24 (9), 091111.
- SAYAG, ROIY & WORSTER, M GRAE 2019a Instability of radially spreading extensional flows. Part 1: Experimental analysis. *Journal of Fluid Mechanics* 881, 722–738.
- SAYAG, ROIY & WORSTER, M GRAE 2019b Instability of radially spreading extensional flows. Part 2: Theoretical analysis. Journal of Fluid Mechanics 881, 739–771.
- SCHOOF, CHRISTIAN & HEWITT, IAN 2013 Ice-sheet dynamics. Annual Review of Fluid Mechanics 45, 217–239.